



MODEL	Body Type		Chamber Size W x L x H inch(mm)	Footprint W x L x H inch(mm)	Conveyor Belt Height* Inches(mm)	Fans	Zones	Max Temp °F(°C)	Voltage**	AMPS	WATTS	Capacity (lbs/hr)		Wire φ	Belt Speed (min)	Weight (lbs)		
	Body Type	Belt Type										@500°F	@750°F					
JN-540	S	TU	5.0x40.5x2.0 (127x1029x51)	19"x59" (482x1473)	Fixed at 24.5" or 28" (622, 711) Option: Jacks +13" adjustment	1	1	999 (540)	240	11	4,800	50	35	.062" 2mm	3~15	345		
JN-855	S	F/TU	8.0x55x3.0 (203x1397x76)	25"x76" (635x1930)	Fixed at 22.5" or 26" (571, 660) Option: Jacks +13" adjustment	1	1	999 (540)	240	21	9,000	195	140	.125" 3mm	4~25	420		
JN-1060	C	TU	10.0x60x3.0 (254x1524x76)	26"x85" (660x2159)	Fixed at 24" or 27.5" (610, 698) Option: Jacks +13" adjustment	1	1	999 (540)	240	21	9,600	300	195	.162" 4mm	6~55	562		
JN-1276	S	F/TU	12.0x76x4.0 (305x1930x102)	32"x102" (812x2591)	Jack: 25-38" (635~965)	2	1	999 (540)	240	35	15,600	400	250	.192" 5mm	10~80	885		
JN-1888	S	F/TU	18.0x88x5.0 (457x2235x127)	38"x123" (965x3124)	Jack: 18-39" (457~991)	2	1	999(540)	240	59	25500	750	525	.312" 8mm	15~85	1,200		
JN-3088	S	F/TU	30.0x88x5.0 (762x2235x127)	50"x123" (1270x3124)	Jack: 18-39" (457~991)	2	1	999(540)	480	45	38,300	975	640	.312" 8mm	15~85	1,500		
JN-18HD	S	F/FW/ TU	18.0x120x6.0 (457x3048x152)	35"x131" (889x3327)	Jack: 24~37" (610~940)	2	1	999 (540)	480	54	46,200	1200	900	.625" 16mm	15~90	1,500		
JN-24HD	S	F/FW/ TU	24.0x120 x6.0 (610x3048x152)	35"x160" (889x4064)	Jack: 25~38" (635~965)	4	2	999 (540)	480	94	54,700	1500	1200	.750" 19mm	15~90	2,400		
JN-30HD	S	F/FW	30.0x120x6.0 (762x3048x152)	46"x160" (1168x4064)	Jack: X +13" (330) adj.	4	1/2	999 (540)	480	104	90,000	2000	1525	.750" 19mm	15~90	3,200		
JN-40HD	S	FW/T	40.0x180x6.0 (1016x4572x152)	56"x220" (1422x5588)	Custom	4	1/2	999 (540)	480	219	189,000	3000	2000	.750" 19mm	20~90	4,000		
JN-52HD	S	FW/T	52x180x6	68x220"	Custom	4	1/2	999 (540)	480	219	214,000	3900	2600	.750" 19mm	20~90	4,800		
High-Temperature Furnace Line												@	@					
												1000F	1200F					
JN-12HDF	S	F/TU	12.0x88x5.0 (305x2235x127)	35"x132" (889x3352)	Jack: 24-37" (609~940)	2	2	1300 (704)	480	36	31,200	625	500	.312" 8mm	20~90	1,500		
JN-18HDF	S	F/TU	18.0x120x4.0 (457x3048x102)	35"x132" (889x4064)	Jack: 24-37" (609~940)	2	1	1300 (704)	480	53	46,200	885	650	.312" 8mm	20~90	1,500		

S = Solid Body
C = Clam Shell

TU = Turned-Up Belt
T = Tray Belt
FW = Flatwire belt
F = Flat Belt

Jack = Jack Belt Height Adjustment

* Custom belt heights are also available

** Can be furnished with other voltage